



BHARATBENZ

CHANGE IS WHAT PUTS US
AHEAD WITH **3526 (8x2)**

PROFIT
TECHNOLOGY **NXT** 



BHARAT6+

Vehicle Dimensions	3526R		3526R Tanker	
Wheel base (mm)	5775	6375	6375	6375
Cabin	Sleeper	Sleeper	Compact Sleeper	Sleeper
Loading span (ft / mm)	25.9 / 7905	27.9 / 8505	32.2 / 9825	27.9 / 8505
Overall Length (mm)	10490	11090	11990	11090
Overall Width (mm)	2,490	2,490	2,490	2,490
Overall Height (mm) (CBC)	2960	2960	2960	2960
Front Overhang (mm)	1485	1485	1485	1485
Rear Overhang (mm)	2555	2555	3455	2555
Ground Clearance (mm)	210	210	210	210
Engine				
Engine Model	6D26 BSVI OBD-II			
Maximum Power (kW)	250hp (186kW) @ 2300 rpm			
Maximum Torque (Nm)	950 Nm @ 1000-1800 rpm			
No. of Cylinders, cc	6,6700			
Transmission				
Gear Box Model & Type	New G85, 6S + 1R & Manual - Synchromesh with OD			
Clutch Type	Single dry plate - Organic			
Clutch Dia (mm)	395			
Power Take off	Optional			
Axle				
Front Axle	IF 7.0 (Forged - Reverse Elliot)			
Rear Axle	RS440 (Single reduction fully floating)			
Rear Axle Ratio	5.875			
Diff. lock status	Yes			
Chassis Frame & Suspension				
Frame Section (D X W X T) (mm)	286 x 70 x 8			
Front Suspension	Parabolic leaf spring			
Rear Suspension	Balancer type			
Anti-roll Bar	Front - Standard fitment			
Brakes				
Service Brake	Pneumatic - Dual line drum brakes with ABS			
Front Brake Size (mm)	410/180			
Rear Brake Size (mm)	410/180			
Air reservoir capacity (L)	100			
Auxillary Brake	Powerful I-brakes			
Steering				
Steering Type	Tilt & telescopic 4 spoke steering wheels with hydraulic power assistance			
Fuel & Electrical System				
Fuel Tank / Filling Capacity (L)	380 / 355		200 / 185	
Adblue Tank / Filling capacity (L)	60 / 51			
Battery Capacity & Voltage	120Ah, 12V x 2			
Performance				
Maximum Gradeability (%)	20.5			
Maximum Geared Speed (kmph)	80		60	
TCD (m)	21.6		23.7	
Tyres				
Pattern & Size	295/90R20, 295/80R22.5 (optional)			
Weight				
Gross Vehicle Weight (kg)	35000			